

SL 2000/2500SY Series

Y-AXIS BOX GUIDE TYPE
HORIZONTAL TURNING CENTER



SMEC Co., Ltd.
157-10, Goldenroot-ro, Juchon-myeon, Gimhae-si,
Gyeongsangnam-do, Korea
Tel +82 55 340 4800 / Fax +82 55 340 4740
www.smecmachinetools.com



SL 2000/2500SY Series

- SL 2000Y
- SL 2000SY
- SL 2500Y
- SL 2500SY
- SL 2500LY
- SL 2500LSY



SL 2000SY Series

SL 2000Y/SY

SL 2500SY Series

SL 2500Y/SY/LY/LSY

Heavy duty, high productivity Y-axis Box Guide type turning center

- Super stable low-center of gravity 30° slant bed with maximized work area
- Significantly reduced non-cutting time for high efficiency machining
- Servo turret to enhance high-speed performance
- Low center of gravity design minimizing vibration and thermal growth for high precision turning

[] : Option

Category		SL 2000AY ASY	SL 2000BY BSY	SL 2500AY ASY	SL 2500BY BSY	SL 2500ALY ALSY	SL 2500BLY BLSY
Swing over bed	mm(inch)	650(25.60)	650(25.60)	650(25.60)	650(25.60)	650(25.60)	650(25.60)
Max turning length	mm(inch)	490(19.30)	450(17.72)	490(19.30)	476(18.75)	1,284(50.56)	1,271(50.04)
Chuck size (Main/Sub)	inch	6"/- 6"/6"	8"/- 8"/6"	8"/- 8"/6"	10"/- 10"/6[8]"	8"/- 8"/6"	10"/- 10"/6[8]"
Spindle bore (Main)	mm(inch)	61(2.41)	76(3.00)	78(3.08)	86(3.39)	78(3.08)	86(3.39)
Spindle speed (Main)	rpm	6,000	4,500	4,500	3,500	4,500	3,500
Spindle speed (Sub)	rpm	- 6,000	- 6,000	- 6,000	- 6,000[4,000]	- 6,000	- 6,000[4,000]
Main Motor (cont./max)	kW(Hp)	11/18.5(14.76/24.81)	11/18.5(14.76/24.81)	11/18.5(14.76/24.81)	18.5/26(24.81/34.87)	11/18.5(14.76/24.81)	18.5/26(24.81/34.87)
Sub-spindle Motor (cont./max)	kW(Hp)	- 5.5/7.5(7.38/10.06)	- 5.5/7.5(7.38/10.06)	- 5.5/7.5(7.38/10.06)	- 5.5/7.5[11/15](7.38/10.06 [14.76/20.12])	- 5.5/7.5(7.38/10.06)	- 5.5/7.5[11/15](7.38/10.06 [14.76/20.12])
Travels X	mm(inch)	235(9.26)	235(9.26)	235(9.26)	235(9.26)	235(9.26)	235(9.26)
Travels Y	mm(inch)	105[±52.5](4.14[±0.27])	105[±52.5](4.14[±0.27])	100[±50](3.94[±1.97])	100[±50](3.94[±1.97])	100[±50](3.94[±1.97])	100[±50](3.94[±1.97])
Travels Z	mm(inch)	580(22.84)	580(22.84)	580(22.84)	580(22.84)	1,375(54.14)	1,375(54.14)
Travels ZB	mm	580(22.84)	580(22.84)	580(22.84)	580(22.84)	1,388(54.65)	1,346(53.00)
No of tool positions	EA	12[24] (BMT55)	12[24] (BMT55)	12[24] (BMT65)	12[24] (BMT65)	12[24] (BMT65)	12[24] (BMT65)

Extensive turning capacity lineup

- Extensive turning capacity lineup to meet customer needs
- Main chuck : 6~10", Sub chuck : 6~8" available
- Turning length : 450~1,280mm available

Wedge type Y-axis with Superb Cutting Performance

- Side milling, off-center drilling
- Wider off-center work range
- Complex shape machining with a single setup

High rigidity, fast response sub spindle and servo tailstock

- Servo tailstock or built-in type sub-spindle available
- Spindle oil cooling standard for sub-spindle
- NC controlled servo-tailstock allows for high speed, high precision machining


User-centric options and convenience features

- 15" large-screen LCD standard
- SMEC HMI and Manual Guide i standard

SL 2000/2500SY Series
Y-AXIS HORIZONTAL TURNING CENTER

Extensive turning capacity lineup


Offers an extensive turning capacity lineup with increased productivity and superb cost- effective performance for customer satisfaction




The SL 2000/2500 SY Series offers an **extensive lineup** with various **chuck sizes, turning lengths** and the addition of a **sub-spindle**.

- A(Main chuck size) : 6", 8", 10"
- B(Sub chuck size) : 6", 8"
- C(Working bar diameter) : $\varnothing$ 51~76mm(0.21"~3.00")
- D(Max turning diameter) : $\varnothing$ 360~395mm(14.18"~15.56")
- E(Max turning length) : 450~1,280mm(17.72"~50.40 ")

Wedge type Y-axis with superb cutting performance



- Side milling, off-center drilling
- Wider off-center work range
- Complex shape machining with a single setup



Category		SL 2000Y/SY	SL 2500Y/SY/LY/LSY
No. of tool positions	ea	12(24)	12(24)
Turret type		BMT55	BMT65
SHANK & BORING BAR SIZE	mm (inch)	$\square$ 25×25, $\varnothing$ 40 ($\square$ 1×1, $\varnothing$ 1.58)	$\square$ 25×25, $\varnothing$ 50 ($\square$ 1×1, $\varnothing$)
Turret indexing time (1station/full turn)	sec	0.15/1	0.15/1
Rotary tool speed	rpm	~6,000	~5,000
Rotary tool motor power (cont/max)	kW (Hp)	3.7/5.5 (4.97/7.38)	3.7/7.5 (4.97/10.06)
Rotary tool torque (cont/max)	N.m (lbs.ft)	17.64/48.42 (694.49/1,890.56)	35.28/95.06 (1,388.98/3,742.52)


High precision, fast response sub-spindle and servo tailstock

Synchronized C1 and C2-axis indexing

Synchronization of the main spindle (C1) and sub-spindle (C2) indexing allows for machining of a variety of complex shapes. All processes from simple turning and milling to multi-axis simultaneous machining can be completed with a single setup.

Sub-spindle oil cooling unit

The sub-spindle is wrapped by an oil jacket cooling system to minimize thermal growth and to ensure high speed, high-accuracy machining through various machining conditions.



Servo (NC controlled) Tailstock

The servo tailstock supports high-speed, high precision machining where the thrust force is NC controlled. The quill thrust force may be adjusted in accord with the workpiece's length and diameter, reducing the cycle time and increasing the productivity.



User-centric options and convenience features



1 User-centric Large 15" OP Panel

The QWERTY-type keyboard and high visibility buttons and effective button placement enhances ease of use

2 Easy coolant tank maintenance

When cleaning the coolant tank, the coolant tank may be removed while leaving the chip conveyor attached to the machine, making it easier to clean and maintain

3 Easy hydraulic valve adjustment


The gauge and hydraulic valves are located at a height that make it easy for the operator to adjust

SL 2000/2500SY Series

Y-AXIS HORIZONTAL TURNING CENTER


Machine Design

All travel axes are comprised of high rigidity box guideways enabling heavy duty cutting and superb productivity




Model	Main/sub chuck size (inch)	Travel [mm (inch)]			
		X-axis	Y-axis	Z-axis	ZB-axis
SL 2000AY ASY	6/- 6/6	235(9.26)	105[±52.5](4.14[±2.07])	580(22.84)	580(22.84)
SL 2000BY BSY	8/- 8/6	235(9.26)	105[±52.5](4.14[±2.07])	580(22.84)	580(22.84)
SL 2500AY ASY	8/- 8/6	235(9.26)	100[±50](3.94[±1.97])	580(22.84)	580(22.84)
SL 2500BY BSY	10/- 10/6	235(9.26)	100[±50](3.94[±1.97])	580(22.84)	565(22.25)
SL 2500ALY ALSY	8/- 8/6	235(9.26)	100[±50](3.94[±1.97])	1,375(54.14)	1,388(54.65)
SL 2500BLY BLSY	10/- 10/6	235(9.26)	100[±50](3.94[±1.97])	1,375(54.14)	1,346(53.00)

Work Range



Unit : mm (inch)

Model	SL 2000 AY/ASY	SL 2000 BY/BSY	SL 2500 AY/ASY	SL 2500 BY/BSY	SL 2500 AY/ALSY	SL 2500 BY/BLSY
Max turning dia	Ø395 (15.56)	Ø395 (15.56)	Ø360 (14.18)	Ø360 (14.18)	Ø360 (14.18)	Ø360 (14.18)
Max turning length	490 (19.30)	450 (17.72)	490 (19.30)	476 (18.75)	1,280 (50.40)	1,265 (49.81)



30° slant bed provides excellent stability during heavy duty cutting

The 30° slant bed with high-torque tubing and ribbed structure provides superb rigidity against twisting and bending, dampening vibration during heavy duty cutting for high precision machining
The use of a slant bed allows for easier access to the workpiece and excellent chip discharge

Providing a large work envelope, ensuring cost effective productivity

SL 2000SY Series(A, B type)

Max turning dia
Ø395mm (15.56 inch)

SL 2500SY Series(A, B type)

Max turning dia
Ø360mm (14.18 inch)

Spindle



The high power motor allows both high precision and high torque machining, improving operator productivity.

SL 2000AY/ASY

Max spindle speed
6,000rpm
Power (cont/Max.)
11/18.5kW (14.76/24.81 Hp)
Torque (cont/Max.)
69.58/156.8N·m (51.32/115.65 lbs·ft)

SL 2000BY/BSY

Max spindle speed
4,500rpm
Power (cont/Max.)
11/18.5kW (14.76/24.81 Hp)
Torque (cont/Max.)
84.45/208.74N·m (62.29/153.96 lbs·ft)

SL 2500AY/ASY/ALY/ALSY

Max spindle speed
4,500rpm
Power (cont/Max.)
11/18.5kW (14.76/24.81 Hp)
Torque (cont/Max.)
186.2/313.1N·m (137.34/230.94 lbs·ft)

SL 2500BY/BSY/BLY/BLSY


Max spindle speed
3,500rpm
Power (cont/Max.)
18.5/26kW (24.81/34.87 Hp)
Torque (cont/Max.)
522.3/734.1N·m (385.23/541.45 lbs·ft)

SL 2000SY_6" SUB Spindle

Max spindle speed
6,000rpm
Power (cont/Max.)
5.5/7.5kW (7.38/10.06 Hp)
Torque (cont/Max.)
40.18/51.94N·m (29.64/38.31 lbs·ft)

SL 2500SY_8" SUB Spindle

Max spindle speed
4,000rpm
Power (cont/Max.)
11/15kW (14.76/20.12 Hp)
Torque (cont/Max.)
140.1/207.8N·m (103.34/153.27 lbs·ft)



[] : Option


Category	Unit	SL 2000AY SL 2000ASY	SL 2000BY SL 2000BSY	SL 2500AY SL 2500ASY	SL 2500BY SL 2500BSY	SL 2500ALY SL 2500ALSY	SL 2500BLY SL 2500BLSY
Spindle bore (main)	mm (inch)	61 (2.41)	76 (3.00)	78 (3.08)	86 (3.39)	78 (3.08)	86 (3.39)
Spindle nose (main/sub)	ASA	A2-5/- A2-5/A2-5	A2-6/- A2-6/A2-5	A2-6/- A2-6/A2-5	A2-8/- A2-8/A2-5 [A2-6]	A2-6/- A2-6/A2-5	A2-8/- A2-8/A2-5 [A2-6]

The high precision Double Row of Cylindrical Roller Bearings and Angular Ball Bearings on the front end of the spindle and the Double Row of Cylindrical Roller Bearings on the back end of the spindle ensure high precision, high speed machining performance

SL 2000/2500SY Series

Y-AXIS HORIZONTAL TURNING CENTER

Turret



BMT milling turret

This 24 tool position (BMT55/BMT65) turret with the largest in class curvic coupling and power hydraulic clamping force is capable of accepting a rotary tool in every tool position and allows a variety of machining operations with a single set-up. The best in class BMT55/BMT65 tool holders ensures high rigidity, high precision machining and with non-stop turret indexing in either direction minimizes the turret index time down to 0.15 seconds per station.


Turret indexing time : **0.15sec**

No. of tool positions :

NS 200SY : **12ea**
(□25×25, Ø40)
(□1"×1", Ø1.58")

NS 2500Y/LY/SY/LSY : **12ea**
(□25×25, Ø50)
(□1"×1", Ø1.97")

Coolant System



Coolant pump (STD) :


4.5bar(1.1kW)

Coolant pump (OPT) :

7, 10, 14.5, 20bar
→ **60Hz(Submerged)**

30~70bar
→ **60Hz(Independent)**

Accessories[Optional]



Oil skimmer

Continuously cleans the coolant by removing waste oils


Tool presetter

Provides faster and more precise tool setup, checking for tool wear and compensation



Autodoor

Used to quickly open/close the operator door via program to increase productivity in an automation line.




Air blow

Used to automatically remove chips from the chuck after machining and used for safe loading of the chuck in an automated line.



Part catcher & conveyor

Used to receive the completed part and discharge them into a container attached to the exterior of the machine.



Chip conveyor

Used to discharge chips created during machining



SMEC FANUC i series



- 15" LCD color display
- High quality designed OP Panel
- Conversational programming, Manual Guide i
- Part program size 2MB
- SMEC Custom S/W

SMEC Custom S/W displayed using MDI's **S1** button or OP Panel's **CUSTOM** button


CUSTOM : Provide operator convenience and improve productivity using the support function for tool management and additional device setting.




M/G-Code check function
Allows the operator to directly read the M/G-Code on the machine for easy application programming



Easy tailstock setting
Easily configure a variety of functions such as travel limiting, origin setting and signal check



Display only the necessary tools and offsets and check the configured counter at the same time
Tool information and setting management mode



PMc alarm check function
When a PMc alarm occurs, the cause and countermeasures are described in detail, making operation and maintenance more convenient



Counter for each T-Code

Manual Guide i (STD)

SMEC's Manual Guide i system enables advanced part program creation and more efficient and faster machining with conversational programming



Check cutting result using cutting simulation



Check cutting path using cutting simulation

Easy program creation and editing

Program creation using advanced part program editing and extensive cutting cycles

Check program using cutting simulations

Program pre-check using realistic cutting simulation

Effective cutting setup

Tool and cutting condition offset data setup based on measurement cycle

Advanced cutting capabilities

Check cutting status such as cutting cycle name and tool icon during the cutting process

Measurement

Feedback of cutting results and tool offset values after cutting

IoT Solution (OPT)



NC-Gate / IoT-Gate

The NC-Gate / IoT-Gate that was developed in-house with our ICT technology is a universal gateway that not only interworks with our machine tools, but machine tools from other manufacturers, robots, automation equipment, and analog / digital sensors as a network device capable of bi-directional communication.

Supported drivers : Fanuc / Mitsubishi / Siemens NC, Modbus TCP, DeviceNet, Profibus, Ethernet, AI/DI/DO



Provides key performance indicators and displays target achievement
Indicators : achievement rate, productivity, process defect rate, equipment and factory usage, quality defect rate, lead time, and average cycle time




Provides figures and graphs of overall equipment effectiveness
Availability, performance, quality, etc.



Provides operation status and alarm information in case of problems in the production line
Provides information about the operation status, speed, production alarms, etc. of each machine



Remote control and operation
Emergency stop switch, program editing, etc.



Problem diagnosis via remote control
Provide remote diagnosis services to users via the IIoT solution


SL 2000/2500SY Series

Y-AXIS HORIZONTAL TURNING CENTER

Power-Torque Diagram


SL 2000AY/ASY

Max spindle speed
6,000rpm
Power (cont/Max.)
11/18.5kW(14.67/24.81 Hp)
Torque (cont/Max.)
69.58/156.8N·m
(51.32/115.65 lbs-ft)




SL 2000BY/BSY

Max spindle speed
4,500rpm
Power (cont/Max.)
11/18.5kW(14.67/24.81 Hp)
Torque (cont/Max.)
84.45/208.74N·m
(62.29/153.96 lbs-ft)




SL 2000SY_6" SUB Spindle

Max spindle speed
6,000rpm
Power (cont/Max.)
5.5/7.5kW(7.38/10.06 Hp)
Torque (cont/Max.)
40.18/51.94N·m
(29.64/38.31 lbs-ft)



SL 2000SY_MILL Motor


Max spindle speed
5,000rpm
Power (cont/Max.)
3.6/6.6kW(4.83/8.86 Hp)
Torque (cont/Max.)
17.64/48.02N·m
(13.02/35.42 lbs-ft)



Power-Torque Diagram


SL 2500AY/ASY/ALY/ALSY

Max spindle speed
4,500rpm
Power (cont/Max.)
11/18.5kW(14.76/24.81 Hp)
Torque (cont/Max.)
186.2/313.1N·m
(137.34/230.94 lbs-ft)




SL 2500BY/BSY/BLY/BLSY

Max spindle speed
3,500rpm
Power (cont/Max.)
18.5/26kW(24.81/34.87 Hp)
Torque (cont/Max.)
522.3/734.1N·m
(385.23/541.45 lbs-ft)




SL 2500SY_8" SUB Spindle

Max spindle speed
4,000rpm
Power (cont/Max.)
11/15kW(14.76/20.12 Hp)
Torque (cont/Max.)
140.1/207.8N·m
(103.34/153.27 lbs-ft)



SL 2500SY_MILL Motor

Max spindle speed
5,000rpm
Power (cont/Max.)
5.5/15kW(7.38/20.12 Hp)
Torque (cont/Max.)
35.28/95.06N·m
(26.03/70.12 lbs-ft)



SL 2000/2500SY Series


Y-AXIS HORIZONTAL TURNING CENTER

Cutting Performance

Test conditions : SL 2500BSY(8"), Material : SM45C


O.D Cutting

Cutting dia.	mm(inch)	Ø67(2.64)
Cutting depth	mm(inch)	5(0.20)
Cutting speed	m/min(ipm)	210(8,267.72)
Spindle speed	rpm	998
Feedrate	mm/rev(inch/rev)	0.5(0.020)
Chip removal rate	cc/min(oz/min)	525(17.56)




U-Drill Cutting

U-drill dia.	mm(inch)	Ø60(2.37)
Cutting speed	m/min(ipm)	130(5,118.12)
Spindle speed	rpm	670
Feedrate	mm/rev(inch/rev)	0.22(0.009)
Chip removal rate	cc/min(oz/min)	286(9.68)




Tap

Tap size	mm	M22×2.5
Cutting depth	mm(inch)	30(1.19)
Cutting speed	m/min(ipm)	25(984.26)
Spindle speed	rpm	362
Feedrate	mm/rev(inch/rev)	2.5(0.099)



Endmill

Endmill dia.	mm(inch)	Ø20(0.79)
Cutting depth	mm(inch)	5(0.20)
Cutting speed	m/min(ipm)	100(3,937.008)
Spindle speed	rpm	1,592
Feedrate	mm/min(ipm)	100(3.94)
Chip removal rate	cc/min(oz/min)	64(2.17)




※ The above data is based on internal testing. Values may change depending on cutting conditions.


Machine Dimensions

Unit : mm(inch)

Top view




Front view




Model	A (Machine front)	B (Machine side)	C	D (Machine height)	E	F
SL 2000Y/SY	2,790(109.85)	1,752(68.98)	1,324(52.13)	2,095(82.49)	860(33.86)	4,114(161.97)
SL 2500Y/SY	3,643(143.43)	1,930(75.99)	1,204(47.41)	2,085(82.19)	913(35.95)	4,847(190.83)
SL 2500LY/LSY	4,123(162.33)	2,030(79.93)	1,436(56.54)	2,090(82.29)	885(34.85)	6,153(242.25)

Y-AXIS HORIZONTAL TURNING CENTER


SL 2000Y



SL 2500Y/LY



SL 2500SY/LSY



SL 2000/2500SY Series


Y-AXIS HORIZONTAL TURNING CENTER

Work Range


SL 2000AY/BY

Unit : mm(inch)

O.D Tool




I.D Tool




SL 2000ASY/BSY

O.D Tool



I.D Tool




Work Range


SL 2500AY/BY

Unit : mm(inch)

O.D Tool




I.D Tool




SL 2500ASY/BSY

O.D Tool



I.D Tool




Work Range


SL 2500ALY/BLY

Unit : mm(inch)

O.D Tool




I.D Tool




SL 2500ALSY/BSLY

O.D Tool




I.D Tool



Tooling System

Unit : mm(inch)



Standard Tooling


Item / Description			SL 2000Y/SY	
			Y	SY
Static Holder	Block, Clamp		4	7
	OD Holder		2	1
	OD Holder	Double	-	1
	OD Holder	Double (Front)	1	1
	OD Holder	Double (Sub)	-	1
Boring Holder	Face Holder		1	1
	ID Holder		2	1
	ID Holder	Double	1	1
	U-Drill Holder		1	-
Milling Holder	U-Drill Holder	Double	-	1
	Axial Milling Holder		2	2
Socket	Radial Milling Holder		2	2
	Boring	Ø10(Ø3/8")	1	1
		Ø12(Ø1/2")	1	1
		Ø16(Ø5/8")	1	1
		Ø20(Ø3/4")	1	1
		Ø25(Ø1")	1	1
		Ø32(Ø1 1/4")	1	1
	Drilling	MT2	1	1
		MT3	1	1
	ER Collet		-	-

SL 2000/2500SY Series

Y-AXIS HORIZONTAL TURNING CENTER

Tooling System

Unit : mm(inch)



Standard Tooling

Item / Description			SL 2500Y/SY		SL 2500LY/LSY	
			Y	SY	LY	LSY
Static Holder	Block, Clamp		4	7	4	7
	OD Holder		4	1	4	1
	OD Holder	Double	-	3	-	3
	OD Holder	Double (Front)	-	-	-	-
	OD Holder	Double (Sub)	-	-	-	-
	Face Holder		-	-	-	-
Boring Holder	ID Holder		-	-	-	-
	ID Holder	Double	-	-	-	-
	U-Drill Holder		4	-	4	-
	U-Drill Holder	Double	-	4	-	4
Milling Holder	Axial Milling Holder		2	2	2	2
	Radial Milling Holder		2	2	2	2
Socket	Boring	Ø10(Ø3/8")	1	1	1	1
		Ø12(Ø1/2")	1	1	1	1
		Ø16(Ø5/8")	1	1	1	1
		Ø20(Ø3/4")	1	1	1	1
		Ø25(Ø1")	1	1	1	1
		Ø32(Ø1 1/4")	1	1	1	1
		Ø40(Ø1 1/2")	1	1	1	1
	Drilling	MT3	1	1	1	1
		MT4	1	1	1	1
	ER Collet		-	-	-	-

Standard / Optional

● : Standard ○ : Optional △ : Discuss X : N/A

Category		SL 2000SY	SL 2500SY	SL 2500LSY
Spindle	3 jaw open-center chuck	●	●	●
	3 jaw closed-center chuck	X	X	X
	Soft jaw (3set)	●	●	●
	Hard jaw (1set)	○	○	○
	Chuck clamp footswitch	●	●	●
	Dual pressure chucking	○	○	○
	C-axis control (0.001")	●	●	●
	Chuck clamp confirmation	●	●	●
	Chuck dual footswitch	○	○	○
Turret	Tool holder	●	●	●
	Rotary holder type	BMT	●	●
	Rotary holder (axial)	Collet-type, 2EA	●	●
	Rotary holder (radial)	Collet-type, 2EA	●	●
	Rotary holder (axial)	Adapter-type	X	X
	Rotary holder (radial)	Adapter-type	X	X
	Boring bar sleeve (same as U-drill holder sleeve)	●	●	●
	Drill socket	●	●	●
	U-drill holder	●	●	●
	U-drill cap	X	X	X
	Swivel head holder	△	△	△
Tailstock	NC(Servo Motor) tailstock	●	●	●
	Live center (standard with tailstock)	●	●	●
	Tailstock 2 step pressure system	X	X	X
	Quill forward/reverse confirmation	X	X	X
	Tailstock footswitch	X	X	X
Coolant & Air Blow	Standard coolant (nozzle)	○	○	○
	Coolant above chuck	○	○	○
	Coolant gun	○	○	○
	TSC for chuck (for special chuck)	△	△	△
	TSC for sub-spindle (work ejector required)	○	○	○
	Bed flushing	X	X	X
	Air blower	○	○	○
	Rotary tool holder TSC	○	○	○
	Sub-spindle air blower	○	○	○
	Turret tool air blower	X	X	X
	Air gun	○	○	○
	Through spindle air blower (for special chuck)	△	△	△
	Through spindle air blower for sub-spindle (work ejector required)	X	X	X
Coolant pump	4.5Bar	●	●	●
	7Bar	○	○	○
	10Bar	○	○	○
	14.5Bar	○	○	○
	20Bar	○	○	○
	Power coolant system (for automation solutions)	△	△	△
Coolant chiller		○	○	○
Chip Disposal	Coolant tank	●	●	●
	Chip conveyor (Hinge / Scraper)	Side	●	●
		Rear	△	△
	Special chip conveyor (drum filter)		△	△
	Chip bucket	Fixed 380L	○	○
Safety Features	Door interlock	●	●	●
	Torque limiter	●	●	●
	Full splash guard	●	●	●
	Chuck hyd pressure interlock	△	△	△
Electrical	3 step patrol lamp and buzzer	●	●	●
	Lamp for electrical cabinet	○	○	○
	Remote MPG	○	○	○
	Work counter	Digital	○	○
	Total counter	Digital	○	○
	Tool counter	Digital	○	○
	Multi counter	6EA	○	○
		9EA	○	○
	Grounded circuit breaker	○	○	○
	AVR(Auto Voltage Regulator)	○	○	○
	Transformer	25kVA	○	○
		30kVA	○	○
	Auto Power Off	○	○	○
Measurement	Tool Presetter	Manual	○	○
	Tool Presetter	Auto	○	○
	Air zero measuring device (for special chuck)	TACO	△	△
		SMC	△	△
	Linear scale	X-axis	○	○
		Y-axis	○	○
		Z-axis	○	○
	Coolant level gauge (requires chip conveyor)		○	○
Environmental	Air conditioner for electrical cabinet		○	○
	Dehumidifier		△	△
	Oil mist collector		○	○
	Oil skimmer		○	○
	MQL(Minimal Quantity Lubrication)		△	△
Automation	Auto door		○	○
	Auto shutter (for automation solutions)		△	△
	Sub controller		△	△
	Barfeeder interface		●	●
	Additional M-codes (4 pairs)		○	○
	Automation interface		○	○
	I/O expansion (including both IN and OUT)	16 contacts	○	○
		32 contacts	○	○
	Parts catcher		○	○
	Parts conveyor (parts catcher required)		○	X
Hydraulic Supply	Standard hydraulic cylinder	Open-center	●	●
	Standard hydraulic unit	35Bar	●	●

※ For detailed information, please contact your local SMEC dealer.

SL 2000/2500SY Series

Y-AXIS HORIZONTAL TURNING CENTER

Machine Specifications

[] : Option

Category		SL 2000Y		SL 2000SY	
		A type	B type	A type	B type
Chuck	Chuck size (main/sub) inch	6"/-	8"/-	6"/6"	8"/6"
Capacity	Swing over bed mm(inch)	650(25.60)	650(25.60)	650(25.60)	650(25.60)
	Swing over cross-slide mm(inch)	540(21.26)	540(21.26)	540(21.26)	540(21.26)
	Max turning diameter mm(inch)	395(15.56)	395(15.56)	395(15.56)	395(15.56)
	Max milling diameter mm(inch)	310(12.21)	310(12.21)	310(12.21)	310(12.21)
	Max turning length mm(inch)	490(19.30)	450(17.72)	490(19.30)	450(17.72)
Spindle	Spindle speed (main/sub) rpm	6,000/-	4,500/-	6,000/6,000	4,500/6,000
	Spindle nose (main/sub) ASA	A2-5/-	A2-6/-	A2-5/A2-5	A2-6/A2-5
	Draw tube ID (main/sub) mm(inch)	52/- (2.05/-)	68/- (2.68/-)	52/36 (2.05/1.42)	68/36 (2.68/1.42)
	Spindle bore mm(inch)	61 (2.41)	76 (3.00)	61 (2.41)	76 (3.00)
	Main spindle motor (cont/max) kW(Hp)	11/18.5 (14.76/28.41)	11/18.5 (14.76/28.41)	11/18.5 (14.76/28.41)	11/18.5 (14.76/28.41)
	Sub-spindle motor (cont/max) kW(Hp)	-	-	5.5/7.5 (7.38/10.06)	5.5/7.5 (7.38/10.06)
Travels	X-axis stroke mm(inch)	235 (9.26)	235 (9.26)	235 (9.26)	235 (9.26)
	Y-axis stroke mm(inch)	105<±52.5>(4.14<±2.07>)	105<±52.5>(4.14<±2.07>)	105<±52.5>(4.14<±2.07>)	105<±52.5>(4.14<±2.07>)
	Z-axis stroke mm(inch)	580 (22.84)	580 (22.84)	580 (22.84)	580 (22.84)
	ZB-axis stroke mm(inch)	580 (22.84)	580 (22.84)	580 (22.84)	580 (22.84)
	X-axis rapid traverse m/min(ipm)	24 (944.89)	24 (944.89)	24 (944.89)	24 (944.89)
	Y-axis rapid traverse m/min(ipm)	10 (393.71)	10 (393.71)	10 (393.71)	10 (393.71)
	Z-axis rapid traverse m/min(ipm)	30 (1,181.11)	30 (1,181.11)	30 (1,181.11)	30 (1,181.11)
	ZB-axis rapid traverse m/min(ipm)	24 (944.89)	24 (944.89)	24 (944.89)	24 (944.89)
Turret	No of tool positions ea	12[24] (BMT55)	12[24] (BMT55)	12[24] (BMT55)	12[24] (BMT55)
	OD tool size mm(inch)	25 (1)	25 (1)	25 (1)	25 (1)
	Boring bar diameter mm(inch)	40 (1.58)	40 (1.58)	40 (1.58)	40 (1.58)
	Indexing time sec	0.15	0.15	0.15	0.15
	Rotary tool speed rpm	5,000	5,000	5,000	5,000
	Rotary tool motor (cont/max) kW(Hp)	3.7/7.5 (4.97/10.06)	3.7/7.5 (4.97/10.06)	3.7/7.5 (4.97/10.06)	3.7/7.5 (4.97/10.06)
Tailstock	Quill diameter mm(inch)	-	-	-	-
	Quill stroke mm(inch)	580 (22.84)	580 (22.84)	-	-
	Quill taper MT	MT5 (Servo motor)	MT5 (Servo motor)	-	-
Machine	Size [with SIDE chip conveyor] L×W×H mm(inch)	2,790[4,125]×1,752×2,085 (109.85[162.41]×68.98×82.09)		2,790[4,125]×1,752×2,085 (109.85[162.41]×68.98×82.09)	
	Weight kg(lb)	3,850 (8,487.80)	3,900 (8,598.03)	4,150 (9,149.19)	4,200 (9,259.42)
	Coolant tank capacity Liter(gal)	170 (44.91)	170 (44.91)	170 (44.91)	170 (44.91)
Electric power supply kVA/V		34/220	34/220	42/220	42/220
Controller		FANUC Oi-TF+, SIEMENS			

※ Design and specifications are subject to change without notice.

Machine Specifications

[] : Option

Category		SL 2500Y		SL 2500SY	
		A type	B type	A type	B type
Chuck	Chuck size (main/sub) inch	8"/-	10"/-	8"/6"	10"/6[8]"
Capacity	Swing over bed mm(inch)	650(25.60)	650(25.60)	650(25.60)	650(25.60)
	Swing over cross-slide mm(inch)	540(21.26)	540(21.26)	540(21.26)	540(21.26)
	Max turning diameter mm(inch)	360(14.18)	360(14.18)	360(14.18)	360(14.18)
	Max milling diameter mm(inch)	374(14.73)	374(14.73)	374(14.73)	374(14.73)
	Max turning length mm(inch)	490(19.30)	476(18.75)	490(19.30)	476(18.75)
Spindle	Spindle speed (main/sub) rpm	4,500/-	3,500/-	4,500/6,000	3,500/6,000[4,000]
	Spindle nose (main/sub) ASA	A2-6/-	A2-8/-	A2-6/A2-5	A2-8/A2-5[A2-6]
	Draw tube ID (main/sub) mm(inch)	68/- (2.68/-)	77/- (3.04/-)	68/36 (2.68/1.42)	77/36[52] (3.04/1.42[2.05])
	Spindle bore mm(inch)	78 (3.08)	86 (3.09)	78 (3.08)	86 (3.09)
	Main spindle motor (cont/max) kW(Hp)	11/18.5 (14.76/28.41)	18.5/26 (24.81/34.87)	11/18.5 (14.76/28.41)	18.5/26 (24.81/34.87)
	Sub-spindle motor (cont/max) kW(Hp)	-	-	5.5/7.5 (7.38/10.06)	5.5/7.5 (7.38/10.06)
Travels	X-axis stroke mm(inch)	235 (9.26)	235 (9.26)	235 (9.26)	235 (9.26)
	Y-axis stroke mm(inch)	100<±50>(3.94<±1.97>)	100<±50>(3.94<±1.97>)	100<±50>(3.94<±1.97>)	100<±50>(3.94<±1.97>)
	Z-axis stroke mm(inch)	580 (22.84)	580 (22.84)	580 (22.84)	580 (22.84)
	ZB-axis stroke mm(inch)	580 (22.84)	580 (22.84)	580 (22.84)	580 (22.84)
	X-axis rapid traverse m/min(ipm)	18 (708.67)	18 (708.67)	18 (708.67)	18 (708.67)
	Y-axis rapid traverse m/min(ipm)	12 (472.45)	12 (472.45)	12 (472.45)	12 (472.45)
	Z-axis rapid traverse m/min(ipm)	24 (944.89)	24 (944.89)	24 (944.89)	24 (944.89)
	ZB-axis rapid traverse m/min(ipm)	24 (944.89)	24 (944.89)	24 (944.89)	24 (944.89)
Turret	No of tool positions ea	12[24] (BMT65)	12[24] (BMT65)	12[24] (BMT65)	12[24] (BMT65)
	OD tool size mm(inch)	25 (1)	25 (1)	25 (1)	25 (1)
	Boring bar diameter mm(inch)	50 (1.97)	50 (1.97)	50 (1.97)	50 (1.97)
	Indexing time sec	0.20	0.20	0.20	0.20
	Rotary tool speed rpm	5,000	5,000	5,000	5,000
	Rotary tool motor (cont/max) kW(Hp)	3.7/5.5 (9.47/7.38)	3.7/5.5 (9.47/7.38)	3.7/5.5 (9.47/7.38)	3.7/5.5 (9.47/7.38)
Tailstock	Quill diameter mm(inch)	-	-	-	-
	Quill stroke mm(inch)	-	-	-	-
	Quill taper MT	MT5 (Servo motor)	MT5 (Servo motor)	-	-
Machine	Size [with SIDE chip conveyor] L×W×H mm(inch)	3,643[4,667]×1,930×2,085 (143.43[183.75]×75.99×82.09)		3,643[4,667]×1,930×2,085 (143.43[183.75]×75.99×82.09)	
	Size [with REAR chip conveyor] L×W×H mm(inch)	3,358×2,478[2,820]×2,085 (132.21×97.56[111.03]×82.09)		3,358×2,478[2,820]×2,085 (132.21×97.56[111.03]×82.09)	
	Weight kg(lb)	5,600 (12,345.89)	5,800 (12,786.82)	5,800 (12,786.82)	6,000 (13,227.74)
	Coolant tank capacity Liter(gal)	173 (45.71)	173 (45.71)	173 (45.71)	173 (45.71)
Electric power supply kVA/V		37/220	45/220	45/220	53[61]/220
Controller		FANUC Oi-TF+, SIEMENS			

※ Design and specifications are subject to change without notice.

SL 2000/2500SY Series

Y-AXIS HORIZONTAL TURNING CENTER

Machine Specifications

Category			SL 2500LY		SL 2500LSY	
			A type	B type	A type	B type
Chuck	Chuck size (main/sub)	inch	8"/-	10"/-	8"/6"	10"/6[8]"
Capacity	Swing over bed	mm(inch)	650(25.60)	650(25.60)	650(25.60)	650(25.60)
	Swing over cross-slide	mm(inch)	540(21.26)	540(21.26)	540(21.26)	540(21.26)
	Max turning diameter	mm(inch)	360(14.18)	360(14.18)	360(14.18)	360(14.18)
	Max milling diameter	mm(inch)	374(14.73)	374(14.73)	374(14.73)	374(14.73)
	Max turning length	mm(inch)	1,284(50.56)	1,271(50.04)	1,284(50.56)	1,271(50.04)
Spindle	Spindle speed (main/sub)	rpm	4,500/-	3,500/-	4,500/6,000	3,500/6,000[4,500]
	Spindle nose (main/sub)	ASA	A2-6/-	A2-8/-	A2-6/A2-5	A2-8/A2-5[A2-6]
	Draw tube ID (main/sub)	mm(inch)	68/-(2.68/-)	77/-(3.04/-)	68/36(2.68/1.42)	77/36[52](3.04/1.42[2.05])
	Spindle bore	mm(inch)	78(3.08)	86(3.09)	78(3.08)	86(3.09)
	Main spindle motor (cont/max)	kW(Hp)	11/18.5(14.76/28.41)	18.5/26(24.81/34.87)	11/18.5(14.76/28.41)	18.5/26(24.81/34.87)
	Sub-spindle motor (cont/max)	kW(Hp)	-	-	5.5/7.5(7.38/10.06)	5.5/7.5[11/15](7.38/10.06[14.76/20.12])
Travels	X-axis stroke	mm(inch)	235(9.26)	235(9.26)	235(9.26)	235(9.26)
	Y-axis stroke	mm(inch)	100<±50>(3.94<±1.97>)	100<±50>(3.94<±1.97>)	100<±50>(3.94<±1.97>)	100<±50>(3.94<±1.97>)
	Z-axis stroke	mm(inch)	1,375(54.14)	1,375(54.14)	1,375(54.14)	1,375(54.14)
	ZB-axis stroke	mm(inch)	1,388(54.65)	1,346(53.00)	1,388(54.65)	1,346(53.00)
	X-axis rapid traverse	m/min(ipm)	18(708.67)	18(708.67)	18(708.67)	18(708.67)
	Y-axis rapid traverse	m/min(ipm)	10(393.71)	10(393.71)	10(393.71)	10(393.71)
	Z-axis rapid traverse	m/min(ipm)	24(944.89)	24(944.89)	24(944.89)	24(944.89)
	ZB-axis rapid traverse	m/min(ipm)	24(944.89)	24(944.89)	24(944.89)	24(944.89)
Turret	No of tool positions	ea	12[24] (BMT65)	12[24] (BMT65)	12[24] (BMT65)	12[24] (BMT65)
	OD tool size	mm(inch)	25(1)	25(1)	25(1)	25(1)
	Boring bar diameter	mm(inch)	50(1.97)	50(1.97)	50(1.97)	50(1.97)
	Indexing time	sec	0.15	0.15	0.15	0.15
	Rotary tool speed	rpm	5,000	5,000	5,000	5,000
	Rotary tool motor (cont/max)	kW(Hp)	3.7/5.5(9.47/7.38)	3.7/5.5(9.47/7.38)	3.7/5.5(9.47/7.38)	3.7/5.5(9.47/7.38)
Tailstock	Quill diameter	mm(inch)	-	-	-	-
	Quill stroke	mm(inch)	1,390(54.73)	1,375(54.14)	-	-
	Quill taper	MT	MT5 (Servo motor)	MT5 (Servo motor)	-	-
Machine	Size [with SIDE chip conveyor] L×W×H	mm(inch)	4,123[5,559]×2,030×2,090 (162.33[218.86]×79.93×82.29)		4,123[5,559]×2,030×2,090 (162.33[218.86]×79.93×82.29)	
	Weight	kg(lb)	7,400(16,314.21)	7,500(16,534.67)	7,500(16,534.67)	7,600(16,755.14)
	Coolant tank capacity	Liter(gal)	250(66.05)	250(66.05)	250(66.05)	250(66.05)
Electric power supply			kVA/V	38/220	46/220	54[63]/220
Controller			FANUC Oi-TF+, SIEMENS			

※ Design and specifications are subject to change without notice.

NC Specification / FANUC

● : STD ○ : Optional X : N/A

Functions		Oi-TF+	Functions		Oi-TF+
Controlled axis	Controlled axes	X, Z, Y, B, C	Program input	Absolute / incremental command	G90/G91
	Max simultaneously controlled axes	4		Repeating canned cycle	●
	Least input increment	0.001mm / 0.0001"		Repeating canned cycle 2	●
	Built-in stroke limit	Soft overtravel 1, 2, 3		Canned cycles	●
	Machine lock	●		Drilling canned cycle	●
Operation functions	Manual handle feed	X1, X10, X100		Decimal point input	●
	Dry run	●		Inch / metric conversion	G20 / G21
	Single block	●		Program restart	●
	Feed per minute	G94		Sub program call	●
	Feed per revolution	G95		Max programmable value	±99999.999mm/±9999.9999"
	DNC operation	Ethernet, CF card		M function	3 digit
Interpolation functions	Thread cutting pause	○		Custom macro	●
	Linear interpolation	G01		Addition of custom macro common variables	#100~#199, #500~#999
	Circular interpolation	G02, G03		Direct drawing dimension programming	●
	Dwell	G04		Programmable data input	G10
	Cylindrical interpolation	G70.1		Tape code	ISO / EIA
	Skip	G31		Optional block skip	●
	Nano smoothing	X		Workpiece coordinate system	G52 ~ G59
	Polar coordinate interpolation	●		Addition of workpiece coordinate system	X
	Reference position (zero) return	G28	Interface function	Embedded ethernet	●
	Reference position (zero) return check	G27		Fast ethernet	X
	2nd, 3rd, 4th reference point return	G30	Setting and display	Alarm and operator history display	●
	Variable lead thread cutting	●		Run hour and parts count display	●
Feed function	Thread repair	●		Loadmeter display	●
	Rapid traverse override	F0, 25%, 50%, 100%		Self diagnosis function	●
	Feedrate override	0~200%		Extended part program editing	●
	Jog override	●		Machining condition selection function	○
	AI look ahead	X		Machining quality level adjustment	X
Spindle function	AI contour control II	○ (200 block)		Display screen	15" color LCD
	Spindle orientation	●		Multi-language display	25 language
	Rigid tapping	M29	Data input/output	Fast data server	X
	Spindle override	S0 ~ 150%		RS232C interface	●
Tool functions	Arbitrary speed threading	○		Memory card input / output	●
	Tool number command	T4-Digt Tool number	Editing operation	USB memory input / output	●
	Tool nose radius compensation	G40 ~ G42		Part program storage size	2Mbyte
	Tool offset pairs	128-pairs		Number of registered programs	1,000 EA
	Tool geometry / wear offset	●		Manual guide Oi	X
	Tool length compensation	X		Manual guide i	●
	Tool life management	●			
	Tool path graphic display	●			